

Dixon Bayco Hose



The Right Connection™

A101R - General Purpose Red

Dixon A101R general purpose hose is suitable for Air or Water service in a wide variety of applications, including but not limited to:
Construction sites, Industrial facilities, Factories, Maintenance departments, Mining, Automotive repair facilities, and Agricultural use.

Application: Air or Water delivery, where oil is not considered a significant factor.

Hose Construction

Inner Tube: Black extruded NR/SBR Blend.

Reinforcement: High strength polyester braid.

Outer Cover: Red extruded SBR/EPDM Blend. Offers excellent Abrasion, Ozone and UV resistance.

Branding: White lettering: "DIXON A101 GENERAL PURPOSE 200 PSI WP {Size}. DIXON HOSE ASSEMBLY W.P. ____"

Working Pressure: 200 Psi at a safety factor of 3:1

Temperature Rating: -25°C to 100°C (-13°F to 212°F)



Part #	ID Inches	OD Inches	Working Pressure	Weight (Lbs per Foot)	Packaging
A101R006	1/4	0.53	200 Psi	0.12	500ft/Reel
A101R010	3/8	0.68	200 Psi	0.16	500ft/Reel
A101R012	1/2	0.83	200 Psi	0.25	500ft/Reel
A101R020	3/4	1.16	200 Psi	0.40	600ft/Reel*
A101R025	1	1.38	200 Psi	0.50	600ft/Reel*
A101R032	1 1/4	1.73	200 Psi	0.77	100ft/Coil
A101R038	1 1/2	2.09	200 Psi	1.15	100ft/Coil
A101R050	2	2.60	200 Psi	1.57	100ft/Coil

* Reel length is made up of 2 x 300ft lengths

Hose is sold by the Reel/Coil length.

Dixon Bayco Hose

A102XP X-High Pressure Contractors Yellow Air

Dixon A102XP Contractors hose is suitable for air or water service in a wide variety of applications, including but not limited to:

Construction sites, Industrial facilities, Factories, Maintenance departments, Mining, and Agricultural use. Conforms to standards BS5118:2 & EN2398

Application: Air or Water delivery.

Hose Construction

Inner Tube: Black extruded NR/SBR Blend, suitable for service with air tool lubricators (oil mist service)

Reinforcement: High strength polyester braid

Outer Cover: Yellow extruded SBR/EPDM Blend. Offers excellent Abrasion, Ozone and UV resistance.

Branding: Black lettering: "DIXON A102 CONTRACTORS AIR HOSE 400PSI WP {Size}. DIXON HOSE ASSEMBLY W.P. ____"

Working Pressure: 400 Psi at a safety factor of 3:1

Temperature Rating: -25°C to 75°C (-13°F to 167°F)



Part #	ID Inches	OD Inches	Working Pressure	Weight (Lbs per Foot)	Packaging
A102XP012	1/2	0.83	400 Psi	0.26	500ft/Reel
A102XP020	3/4	1.14	400 Psi	0.43	600ft/Reel*
A102XP025	1	1.42	400 Psi	0.59	600ft/Reel*

* Reel length is made up of 2 x 300ft lengths

Hose is sold by the Reel length.

Dixon Bayco Limited

536 Avenue Lepine, **Dorval, QC** H9P 2V6
Phone: 514-422-9292 • Toll-Free 877-963-4966
Fax: 866-422-0166

2315 Bowman Street, **Innisfil, ON** L9S 3V6
Phone: 705-436-1125 • Toll-Free 877-963-4966
Fax: 877-436-6251

7011 68th Avenue, **Edmonton, AB** T6B 3E3
Phone: 780-469-5444 • Toll-Free 877-963-4966
Fax: 877-463-9205



The Right Connection™

www.dixonbayco.com

Customer Service
877-963-4966